

MEET



FERMAX



IP INTERCOM INTEGRATION IN ACCESS CONTROL AND UNIFIED SECURITY SYSTEMS

MEET is fully integrated in DASSnet, the complete DORLET Security Platform, that allows the unified management of access control, CCTV, intrusion and fire systems. It is possible to manage door lock release, video recording and monitoring in a security software.



IP
TECHNOLOGY

FERMAX

COMMUNICATION



The outdoor panel camera sends continuously and in parallel a secondary RTSP video stream to DORLET DASSnet software,

The panel call from the outdoor visitor panel can be answered directly from the DORLET DASSnet software, or SIP telephone, due to the fact that the call can use the SIP protocol which is compatible with the software.

The outdoor panel sends the card information read by the **integrated MIFARE reader**, to the DORLET control unit. In the same way, DORLET DESFIRE readers can be used when required.

Software Dassnet DORLET



Servidor SIP DORLET



Unidad de Control DORLET



BENEFITS



- ◆ Integration costs can be reduced since the same IP infrastructure can be used for intercom and access control, so no additional wiring is required.



- ◆ It is possible to use MEET outdoor panel camera as a regular CCTV camera thanks to the RTSP stream.



- ◆ The outdoor panel embraces the proximity reader in a clean aesthetic, and at the same time is connected to a DORLET control unit so that door open decisions are taken by the control unit. It is always possible to use DORLET readers with 100% secure technology.

- ◆ The software operator manages from one single interface all the building security, including access control in intercom outdoor panels and independent doors. Moreover, it is possible to control intrusion, CCTV, fire systems and operate automatically over all these systems.

INTEGRATION PROTOCOLS

- ◆ AUDIO CODECS : G.711 (PCMU, PCMA)
- ◆ VIDEO CODECS: H.264 VIDEO RESOLUTION : 1080 x 720p
- ◆ VIDEO STREAMING PROTOCOL: RTSP (Real Time Streaming Protocol)
- ◆ ACCESS CONTROL PROTOCOL WIEGAND 26

WHY FERMAX?

FERMAX is a worldwide reference in the video intercom industry. The products have been installed in the most emblematic projects in the world. FERMAX Distribution network, which is present in more than 70 countries, will provide the best Support and assistance.

MEET PRODUCT REFERENCE NUMBERS



WIT 7" Y 10" INDOOR MONITORS



ref.9533



ref.953303

MILO 1 PUSHBUTTON
OUTDOOR PANEL



MEET ME
CALL DIVERT



KIN PANEL



MARINE PANEL

PANELS

- 9531 **MILO DIGITAL VIDEO PANEL MEET**
- 9532 **MILO TOUCH VIDEO PANEL MEET**
Panel: 155x380x48mm. 1,2 Mpx
- 9536 **DIRECTORY MILO PANEL MEET**
Flush box 143x357x58mm. Flush box not included.
- 9542 **MILO PANEL FLUSH BOX- L MEET**
Flush box 143x357x58mm
- 9517 **MILO DIGITAL PANEL SURFACE BOX MEET**
Flush box: 160x387x66-108mm
- 9533 **1/W MILO VIDEO PANEL MEET**
- 9534 **1/W MILO VIDEO PANEL WITH PROX MEET**
- 953303 **1/W MILO VIDEO BLACK PANEL MEET**
Panel: 118x183x49mm. 1 Mpx.
- 9535 **MEET PROXIMITY READER**
Panel: 118x183x49mm.
- 9543 **MEET PANEL FLUSH - S**
Flush box: 105x172,5x63mm
- 1455 **MARINE DIGITAL VIDEO PANEL MEET**
155x 410x 49mm
- 1459 **MARINE PANEL FLUSH BOX MEET**
141x394x60mm
- 1445 **KIN TOUCH PANEL MEET**
Panel: 185x405x50 mm
- 1449 **KIN PANEL FLUSH BOX MEET**
Panel: 170x382x58 mm

FERMAX INTERCOM INDOOR UNITS

- 14721 **7" WIT MONITOR PoE WHITE**
- 14723 **7" WIT MONITOR PoE BLACK**
1 connector RJ-45. Dimensions: 212x132,5x20mm
- 14831 **10" WIT MONITOR HOME AUTOMATION PoE WHITE**
- 14833 **10" WIT MONITOR HOME AUTOMATION PoE BLACK**
2 connectors R-J45. Dimensions: 270x168x20mm
- 1489 **10" WIT MONITOR FLUSH BOX**
Dimensions: 255x155x50mm
- 9541 **MIO/WIT MONITOR CONNECTOR**
Mounting support for the MIO/WIT monitor on the wall.
Includes monitor connection cables.
- 1496 **MEET ME LICENSE (CALL DIVERT)**
up to 8 simultaneous users with the same license